

REMARKS

This Response responds to the Office Action dated January 27, 2003 in which the Examiner rejected claims 1, 4-6, 8 and 10-15 under 35 U.S.C. §103.

Claim 1 claims an electronic apparatus comprising an electronic circuit board, an electrically conductive casing, a semiconductor element module and a resin fixture. The electrically conductive casing is for encasing the electronic circuit board. The semiconductor element module electrically is connected to the electronic circuit board via a plurality of lead terminals. The semiconductor element module has a column-shaped section. An axis of the column-shaped section is parallel to a direction of extension of the lead terminals. The resin fixture intervenes between the electrically conductive casing and the semiconductor element module. The resin fixture is mounted with the semiconductor element module and is fitted to the electrically conductive casing. The resin fixture has a cylinder-shaped section for retaining, in its inner periphery, the column-shaped section of the semiconductor element module. An outer periphery surface of the cylinder-shaped section is metal plated and an inner periphery surface of the cylinder-shaped section is not metal plated.

Through the structure of the claimed invention having a resin fixture with a cylinder-shaped section for retaining a column-shaped section of a semiconductor element module in its inner periphery, as claimed in claim 1, the claimed invention provides an electronic apparatus which allows the semiconductor element module to be reliably fitted inside the resin fixture and ensures electrical insulation between the semiconductor element module and the casing. The prior art does not show, teach or suggest a column-shaped

section of a semiconductor element module retained inside an inner periphery of a cylinder-shaped section of a resin fixture as claimed in claim 1.

Claims 1 and 8 were rejected under 35 U.S.C. §103 as being unpatentable over *Teruhiro* (Japanese Reference 09-270747) in view of *Hirota* (U.S. Patent No. 6,168,465).

Applicant respectfully traverses the Examiner's rejection of the claims under 35 U.S.C. §103. The claims have been reviewed in light of the Office Action, and for reasons which will be set forth below, Applicant respectfully requests the Examiner withdraws the rejection to the claims and allows the claims to issue.

Teruhiro appears to disclose in Figure 1 a casing 14, a block 16, an opening 18 formed in the casing and an opening 19 formed on each of two opposite side surface of the block 16. The opening 18 and the opening 19 engage with each other. As shown in Figure 6, the assemblies are mounted into the casing 14 in such a manner that the convex portion or opening 19 formed on the side surface of the block 16 fits into the opening or convex portion 18 formed on the side surface of the casing 14. Openings 20a, 20b in the block are formed such that the lead terminals 14a and 14b are individually inserted therein. The lead terminal 40a is soldered to the opening 22a of the flexible substrate and lead terminal 4b is soldered to the opening 22b of flexible substrate.

Thus, *Teruhiro* merely discloses a U-shaped block. Nothing in *Teruhiro* shows, teaches or suggests a resin fixture having a cylinder-shaped section as claimed in claim 1. Rather, *Teruhiro* merely discloses a U-shaped block.

Additionally, *Teruhiro* merely discloses openings 20a, 20b formed in the block 16 for the lead terminals of an optical semiconductor module 3. Nothing in *Teruhiro* shows,

teaches or suggests a resin fixture retaining a column-shaped section of a semiconductor element module in (inside) its inner periphery as claimed in claim 1. Rather, *Teruhiro* merely discloses openings formed in the block for the lead terminals of the module.

Hirota appears to disclose as seen in FIG. 8, a plurality of terminals 22 each having a shell 3 are placed together on an attachment base 2, which in turn is fixed to the converter body 21 with screws 4. (col. 7, lines 43-46) A terminal joint module is composed of a plate-like attachment base 2 and a plurality of cylindrical shells (outer conductors) 3 placed together on the attachment base 2, and is fixed to the outer side of the converter body 1 with screws 4 in both ends thereof. The attachment base 2 and shells 3 are formed of the same material by the die-cast process. A rib 5 is provided between neighboring shells 3 in order to improve molding performance. Shells 3 are formed by the roll-forming process using a metal die or by other methods. It is advantageous that the metal die to be used in this case has a thread formed on the inner side thereof. By this configuration, it is possible to form a male thread on the outer peripheral side of the shell 3 when it is formed. A metal contact 6 as a core conductor is inserted at the center of the shell 3. A plurality of terminal holes 1a are formed for corresponding metal contacts 6 while a packing 7 is fitted on the outside surface of the converter body 1 so as to enclose all the terminal holes 1a. Thus, each output terminal 8 is constituted by the combination of the shell 3 and the metal contact 6. (col. 8, lines 1-21) FIGS. 12A and 12B show a third embodiment of a terminal structure of the receiver-side converter. FIG. 12A is a partial sectional-side view and FIG. 12B is a bottom view. In the terminal structure of this embodiment, the attachment base 2 is formed of a plastic molding. Metallic shells 3 (with male thread on the outer peripheral

side) formed by machining, roll-forming or other processes are inserted when fused plastic is molded to a die, whereby the fused plastic flows around the shells 3 and is cured as it is cooled to form an integral structure of the attachment base 2 with the shells 3 fixed. (col. 8, lines 54-64) FIGS. 14A and 14B show an embodiment in which inner parts 14 constituting output terminals 8 are formed by resin molding. When formed, inner parts 14 are integrally molded with connecting members 15 to form a blocked series of inner parts 14. The thus formed blocked series of several inner parts is inserted together, as shown in FIG. 14A, into a continuous series of terminal joint modules each composed of an attachment base 2 and shells 3. In this operation, when blocked inner parts 14 are inserted into the shells 3, connecting members 15 between inner parts 14 are punched away while the inner parts 14 are assembled in place by press-fitting (see FIG. 14B). (col. 9, lines 17-28) In contrast to the above comparative example, an attachment base 2 with a multiple number of terminal shells 3 is fixed to the converter body 1 with screws 4 to form a multiple terminal structure as seen in FIGS. 17A and 17B. (col. 10, line 66 through col. 11, line 2)

Thus, *Hirota* merely discloses metallic shells 3 having a male thread on an outer peripheral side and having resin inner parts 14 inserted into the shells 3 to form the output terminals 8. Thus nothing in *Hirota* shows, teaches or suggests or suggests a resin fixture retaining a column-shaped section of a semiconductor element module in (inside) its inner periphery as claimed in claim 1. Rather, the metallic shells 3 of *Hirota* with the male connector clearly indicate that the cable plug mates therewith through a female connector

and thus the female connector would surround the male threaded metallic shells rather than be retained in (inside) an inner periphery of a cylinder-shaped section of a resin fixture.

A combination of *Teruhiro* and *Hirota* would merely suggest to replace the U-shaped block 16 with the openings 20a, 20b of the *Teruhiro* for a male threaded metallic shell 3 to attach to a cable plug as taught by *Hirota*. Thus nothing in the combination of *Teruhiro* and *Hirota* show, teach or suggest a resin fixture having a cylinder-shaped section for retaining, in its inner periphery, a column-shaped section of a semiconductor element module as claimed in claim 1. Therefore, Applicant respectfully requests the Examiner withdraws the rejection to claim 1 under 35 U.S.C. §103.

Claim 8 depends from claim 1 and recites additional features. It is respectfully submitted that claim 8 would not have been obvious within the meaning of 35 U.S.C. §103 over *Teruhiro* and *Hirota* at least for the reasons as set forth above. Therefore, it is respectfully requested that the Examiner withdraws the rejection to claim 8 under 35 U.S.C. §103.

Claims 4-6 and 10-15 were rejected under 35 U.S.C. §103 as being unpatentable over *Teruhiro* and *Hirota* and further in view of *Suzuki et al.* (U.S. Patent No. 5,073,047).

Applicant respectfully traverses the Examiner's rejection of the claims under 35 U.S.C. §103. The claims have been reviewed in light of the Office Action and for reasons which will be set forth below, it is respectfully requested that the Examiner withdraws the rejection to the claims and allows the claims to issue.

As discussed above, since nothing in the combination of *Teruhiro* and *Hirota* show, teach or suggest the primary features as claimed in claim 1, Applicant respectfully submits

that the combination of *Teruhiro* and *Hirota* with a secondary reference of *Suzuki et al.* will not overcome the deficiencies of the primary references. Therefore, Applicant respectfully requests the Examiner withdraws the rejection to claims 4-6 and 10-15 under 35 U.S.C. §103.

Thus it now appears that the application is in condition for reconsideration and allowance. Reconsideration and allowance at an early date are respectfully requested.

If for any reason Examiner feels that the application is not now in condition for allowance, it is respectfully requested that the Examiner contact, by telephone, the Applicant's undersigned attorney at the indicated telephone number to arrange for an interview to expedite the disposition of this case.

In the event that this paper is not timely filed within the currently set shortened statutory period, Applicant respectfully petitions for an appropriate extension of time. The fees for such extension of time may be charged to our Deposit Account No. 02-4800.

In the event that any additional fees are due with this paper, please charge our Deposit Account No. 02-4800.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

By: 

Ellen Marcie Emas

Registration No. 32,131

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620
Date: April 8, 2003